



SELECT™ LED Flood Light

HOT

Optional External Power & CCT Switch,
Motion Sensor, Photocell Sensor



Common Attributes

CCT Tunable	Color Temperature			
	5000K	4000K	3000K	
Power Tunable	USA-FL-30W	15W	20W	30W
	USA-FL-55W	20W	30W	55W
	USA-FL-100W	55W	75W	100W

► DESCRIPTION

This Select™ LED Flood Light is 3CCT/Watts selectable. It is suitable for most outdoor and area lighting application including wet conditions. In addition to diminishing energy costs, the fixtures virtually eliminate maintenance expenses with an L70 lifetime of 50,000 hours.

► MODEL NUMBER(S)

Model No.	Watts (W)	Input Voltage	Lumens	CCT (K)	G.W (kg)
USA-FL-30W-D-YY	30	120-277Vac	130LM/W	5700K	10.09
USA-FL-30W-CS-TUNE	30	120-277Vac	130LM/W	3000/4000/5000K	10.09
USA-FL-55W-D-YY	55	120-277Vac	130LM/W	5700K	9.22
USA-FL-55W-CS-TUNE	55	120-277Vac	130LM/W	3000/4000/5000K	9.22
USA-FL-100W-D-YY	100	120-277Vac	130LM/W	5700K	3.86



► DIMENSIONS

